



KIRLOSKAR BROTHERS LTD.

SHOWER JOY PRESSURE BOOSTER SYSTEM



FEATURES: Constant & uniform pressure supply in pipeline, Auto ON & OFF when the tap is open or close, Give uniform pressures on all floors in multi-storey building & apartment, Robust, rust free & user-friendly, Ready to use, Available in stainless steel body

APPLICATION: To supply water from sumps /overhead tank to intermittent & variable demand to get uniform water pressure, To supply water from overhead tank to intermittent & variable demand to get uniform pressure at every floor.

BROAD APPLICATION AREAS: Multi-storey Buildings & Bungalows, Industries, Hotel, Garages, Lawn & Gardening, Clubs, Hospitals

MATERIAL OF CONSTRUCTION: Pump casing : SS, Motor body: Aluminum die cast, Impeller / : Engineering plastic /Stainless steel, Diffuser: Engineering plastics, Shaft: SS,

MOTOR: Induction motor :2900rpm, Insulation: Class B, Protection : IP44, Rated ,220volts

STAGE	SHOWER JOY-PBS	KW /HP	TANK SIZE in LTRS	HEAD RANGE(m)	FLOW RANGE(lpm)	APPROX.NO OF OUTLETS(TAPS)	Min & Max Pr Setting(Kg/Cm ²)
MULTISTAGE	SJ-72824MS	0.75/1.0	24	28-15	35- 65	7	1.4-2.8
	SJ-83224MS	1.1/1.5	24	40- 15	30-72	8	1.8-3.2
	SJ-63824MS	1.1/1.5	24	45-28	36-60	6	1.8-3.8
SINGLE STAGE	SJ-42420	0.37/0.5	20	15-10	24-40	4	1.4-2.4
	SJ-32820	0.55/0.75	20	30-10	09-40	3	1.4-2.8
	SJ-52820	0.75/1.0	20	25-15	30-48	5	1.4-2.8
	SJ-42820	1.1/1.5	20	39-20	10-40	4	1.4-2.8
	SJ-53220	1.1/1.5	20	37-20	24-48	5	1.8-3.2

Authorised Distributor Perfect Industrial Services
 34&5, CENTRE POINT, OPP PIPARIA POLICE STN, Silvassa-396230 (DNH)
 Tel.: 0260-2633225, Fax: 0260-2632518, Cell: 9375122207/9824122207
 E-mail: info@perfectindustrial.com, www.perfectindustrial.com